

Chassis Selection Guide

Model No.	Type	Board Type		Max. slots	Drive Capacity				Fan Spec.			
		Slot SBC	Motherboard		5.25" F.P.	3.5" F.P.	2.5" Int	3.5" Int	4cm	6cm	8cm	12cm
RACK-1150G	1U	PICMG 1.0 full-size		3	1			1	3			
RACK-1151G	1U	PICMG 1.0 full-size		3	1			1	3			
RACK-220G	2U	PICMG 1.0 full-size	*MicroATX, Mini-ITX	6	1	1		1			2	
RACK-221G	2U	PICMG 1.3 full-size		6	1	1		1			2	
RACK-2000G	2U	PICMG 1.0 full-size		6	1	1		1			2	
RACK-2100G	2U	PICMG 1.3 full-size		6	1	1		1			2	
RACK-1350G	3U		ATX, MicroATX, Mini-ITX	7	2	1		1		**2	2	
RACK-3400G	4U	half-size		10	2	1					2	
RACK-305G	4U	full-size	*ATX, MicroATX, Mini-ITX	14	2	1		1		***2	2	
RACK-360G	4U	full-size	*ATX, MicroATX, Mini-ITX	14	2	1		1		***2		1
RACK-814G	4U	full-size		14	1	1		1			3	
RACK-3000G	4U	full-size	*ATX, MicroATX, Mini-ITX	14	3	2		1		***2	2	
RACK-3200G	4U	full-size		20	+6	1					4	
RACK-4000	4U	full-size		8			4				4	
RACK-500G	5U	full-size		5		1		1			1	
RACK-900G	5U	PICMG 1.0 full-size		10	1	1		1			2	
RACK-3035G	7U	full-size		20	+6						5	
PAC-42GF		full-size		4		1	▲2				1	
PACO-504F		full-size		4				2				
PACO-506F		full-size		6				2				
PAC-1000G		full-size		6	1	1		1			1	
PAC-106G		full-size		6		1		1			1	
PAC-107G		full-size		6	1	1		1			1	
PAC-1700G		full-size		7	1	1		2			1	
PAC-125G		full-size		10	2	1		1			1	
PAC-130G		full-size	*MicroATX, Mini-ITX	10	2	1					2	
PAC-53GH		half-size		3			1					
PAC-54GH		PICO/PICOe		3			1			1		
PR-1300G		half-size		3		1				1		
PAC-42GH		half-size		4		△1		△1			1	
PACO-504H		half-size		4				2				
PR-1500G		half-size		5	◇1	1		1			1	
PAC-400G		half-size		5				△1			1	
PAC-52G		half-size		6								
PACO-506H		half-size		6				2				
PAC-700G		half-size		7	1	△1		1			1	
EBC-1000G			WAFER Series				1		1			
EBC-2100			NANO Series				1		**1			
EB-2850G			NOVA Series									

- Rackmount chassis
- Full-size wall mount chassis
- Half-size wall mount chassis
- Embedded chassis

* for ATX model
 ** optional
 *** optional fans for ATX model

◇ slim-type CD-ROM
 △ Please refer to datasheet for detail information
 † Each 5.25" space can be changed to 3.5"(F.P. or HDD) with optional bracket
 ▲ PAC-42GF can accommodate 2 x 2.5"HDD or 2 x 3.5" HDD

Chassis Selection Guide

Indicators		Front Panel Control					PSU	Dimensions(mm)			Color		
Power	HDD	Power	reset	KB connector	USB	keylock		Depth	Height	Width	Black	White	Other
X	X	X	X		2		1U	449	44	431	X		
X	X	X	X		2		1U	440	44	431	X		
X	X	X	X		2	X	PS/2	487.5	88	431	X	X	
X	X	X	X		2	X	PS/2	487.5	88	431	X	X	
X	X	X	X			X	PS/2, redundant	576.9	88	431	X	X	
X	X	X	X		2	X	PS/2, redundant	576.9	88	431	X	X	
X	X	X	X		2	X	2U	480	133	431	X		
X	X	X	X			X	PS/2 or mini redundant	283	176	431	X	X	
X	X	X	X	X	2	X	PS/2 or mini redundant	413	176	431	X	X	
X	X	X	X	X	2	X	PS/2 or mini redundant	435.5	176	431	X	X	
X	X	X	X		2	X	PS/2 or mini redundant	454.7	176	431	X		
X	X	X	X			X	PS/2 or mini redundant	520	176	431	X	X	
X	X	X	X			X	PS/2 or mini redundant	674	176	431	X	X	
X	X	X	X		8		1U	460	176	431	X		
X	X	X	X		2		1U	440.2	221.3	110.6	X	X	
X	X	X	X		2		1U	440.2	221	221	X		
X	X	X	X		2	X	2 x PS/2 redundant	504	311	431	X		
X	X	X	X		2		1U	405	200	140		X	
							N/A	362	158	124			
							N/A	365.8	157	170			
X	X	X	X				PS/2	421	176	232	X		
X	X	X	X		2		1U	400	175.5	166		X	
X	X	X	X		2		1U	400	218.5	166		X	
X	X	X	X				PS/2	433	253.7	192.4	X		
X	X	X	X		2	X	PS/2	420	176	321		X	
X	X	X	X		2		PS/2	350	176	350	X		
X	X	X	X		2		1U	218	200	95		X	
X	X	X	X		2		1U	253	200	95		X	
X	X	X	X		2		1U	254	88	265		X	
X	X	X	X		2		1U	269	230	140		X	
							N/A	362	124	158			
X	X	X	X		2		1U	254	132	286		X	
X	X	X	X		2		1U	269	230.5	140		X	
X			X		1		N/A	218	147	152.2		X	
							N/A	226	157	170			
X	X	X	X		2	X	1U	279	176	321	X		
X	X	X	X				ACE-890 Series open frame	130	116	172.2	X		
		X					12VDC power adaptor	134	56	262			Gray
X	X	X	X		2		1U						

1
Single Board Computer

2
VIDEO CARD

3
Xscale Solutions

4
Open HMI

5
VITO Universal Controller

6
DINO BLADE

7
LCD Product Series

8
Embedded System

9
Industrial Computer Chassis

10
Power Supply

11
Peripherals